Installation Instructions
3D File
Photometry
Dialux | ULD
Revit


Micro ø57mm

Leds C4 Team

05-9881-Z5-CL

Spotlight IP65 Micro ø57mm LED 3W 3000K Urban grey 343lm





TECHNICAL FEATURES

IP65 IK04 ±90º

Power (W) : 3W

Total power consumption of light (W) : 4.7W

Real lumens : 343

Real lm/W : 73

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Lens / reflector angle : SPOT 17º

Structure material : Aluminium

Structure finish : Urban grey

Diffuser material : Glass

Diffuser finish : Transparent

Useful life : 50.000h L80B20

Equipment included : Yes, electronic

Voltage / frequency : 100-240V/50-60Hz

Warranty : 5 Years

Max. temperature : 25ºC

Seaside : Yes

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED CREE

Luminance C0º65º: 2285

Luminance 90º65º: 2285

CRI: 80


MacAdam steps: 2

Photobiological risk: RG1

UGR

UGR crosswise: 15.0

UGR lengthwise: 15.0





LOGISTICS

Net weight (kg): 0.54

Packaged weight (kg): 0.65

Packaging: 100mm x 100mm x 180mm

12 Un