LEDS C4

Installation Instructions
3D File
Photometry


Suv

Leds C4 Team

05-E046-Z5-CL

Spotlight IP66 Suv LED 4.5W 3000K Urban grey 434lm





TECHNICAL FEATURES

IP66 IK06 ±90º

Power (W) : 4.5W

Total power consumption of light (W) : 5.5W

Real lumens : 434

Real lm/W : 79

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Tipus Regulació : ON-OFF

Lens / reflector angle : MEDIUM 23º

UGR : <=16

Structure material : Aluminium

Structure finish : Urban grey

Diffuser material : Glass

Diffuser finish : Transparent

Voltage / frequency : 100-240V/50-60Hz

Power Factor : 0.50

Useful life : 50.000h L80B20

Max. temperature : 25ºC

Warranty : 5 Years

Seaside : Yes

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED CREE

CRI: 80


MacAdam steps: 2


Photobiological risk: RG1

UGR

UGR crosswise: 12.0

UGR lengthwise: 12.0





VENTILATION FEATURES

Power used: 5.5W

Service value measurement standard: EN 60879:2019

LOGISTICS

Net weight (kg): 0.36

Packaged weight (kg): 0.44

Packaging: 95mm x 95mm x 170mm

20 Un

ACCESSORIES INCLUDED



Spiked post

OPTIONAL ACCESSORIES



71-E112-00-00

IP68 anti-condensation connector with two inlets

Structure material: Technopolymer
Dimensions: 23 x 88 x NA
Net weight (kg): 0.04



71-E122-00-00

IP68 anti-condensation connector with four inlets

Structure material: Technopolymer
Dimensions: 54 x 88 x 28
Net weight (kg): 0.09



71-9199-05-05

IP68 connector with six inlets

Structure material:
Dimensions: NA x NA x NA
Net weight (kg): 0.26



71-9262-05-05

IP67 connector with three inlets

Structure material:
Dimensions: NA x NA x NA
Net weight (kg): 0.09