LEDS C4


Installation Instructions
3D File
Photometry
Dialux | ULD
Revit

Tiny Short

05-E146-Z5-CL

Recessed wall lighting IP66 Tiny Short LED 1.9W 3000K Urban grey 18lm





TECHNICAL FEATURES

IP66 IK10

Power (W) : 1.9W

Total power consumption of light (W) : 2.9W

Real lumens : 18

Real lm/W : 6

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Lens / reflector angle : FLOOD 61º

Structure material : Aluminium

Structure finish : Urban grey

Diffuser material : Glass

Diffuser finish : Sandblasted

Useful life : 50.000h L80B20

Equipment included : Yes, electronic

Brand : HEP

Voltage / frequency : 220-240V/50-60Hz

Warranty : 5 Years

Max. temperature : 50ºC

Seaside : Yes

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED BRIDGELUX


Luminance C0º65º: 18.8


Luminance 90º65º: 204.2

CRI: 80

MacAdam steps: 3

Photobiological risk: RG1





LOGISTICS

Net weight (kg): 0.53

Packaged weight (kg): 0.6

Packaging: 88mm x 96mm x 48mm

30 Un