LEDS C4


Installation Instructions
3D File
Photometry
Dialux | ULD
Revit

Tiny Large

05-E147-Z5-CL

Recessed wall lighting IP66 Tiny Large LED 5.9W 3000K Urban grey 74lm





TECHNICAL FEATURES

IP66 IK10

Power (W) : 5.9W

Total power consumption of light (W) : 7.8W

Real lumens : 74

Real lm/W : 9

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Lens / reflector angle : FLOOD 69º

Structure material : Aluminium

Structure finish : Urban grey

Diffuser material : Glass

Diffuser finish : Sandblasted

Useful life : 50.000h L80B20

Equipment included : Yes, electronic

Brand : HEP

Voltage / frequency : 220-240V/50-60Hz

Warranty : 5 Years

Max. temperature : 50ºC

Seaside : Yes

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED BRIDGELUX


Luminance C0º65º: 46.8


Luminance 90º65º: 2863

CRI: 80

MacAdam steps: 3

Photobiological risk: RG1





LOGISTICS

Net weight (kg): 0.81

Packaged weight (kg): 0.91

Packaging: 171mm x 96mm x 48mm

16 Un

LIGHT APPLICATION

