TABLE - 4 WINDOW PROFILES / SECTION MATRIX

REVISED ON 24TH APRIL 2012

HEIGHT OF BUILDING 0 TO 70 M - GF TO 20 TH FLOOR - 1.5 Kpa

HEIGHT OF BUILDING 71 M TO 100 M - 21ST FLOOR TO 30TH FLOOR - 2 Kpa

ID MARK	CONFIGUARATION	SIZE		Aluminium Series For Frame Jindal Code No. & Wt Kg/Mtr				Aluminium Series For Shutter Jindal Code No. & Wt Kg/Mtr			Glass	Aluminium Series For Frame Jindal Code No. & Wt Kg/Mtr				Aluminium Series For Shutter Jindal Code No. & Wt Kg/Mtr			Glass	Coating	Hardware etc
		WIDTH	HEIGHT	ALUMINIUM SECTION SERIES	Bottom	Top	Side	Bearing Bottom & Top	Interlock Section	Handle Section		ALUMINIUM SECTION SERIES	Bottom	Top	Side	Bearing Bottom & Top	Interlock Section	Handle Section			
SLIDING DOORS																					
SD1	3 TRACK 6 SHUTTERS	6000	2100 TO 2400	30 SERIES JINDAL OR 35X75 SERIES GEETA	20928 (2.032 KG/M) 124 X 51 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	CUSTOM DESIGN	CUSTOM DESIGN 170 MM X 40 MM X 2 MM THK HOLLOW SECTION SS TIP TRACKS			CUSTOM DESIGN 75 MM X 50 MM X 1.8 MM THK HOLLOW SECTION WITH STIFFNERS			SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN / GIESSE MAKE OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SD2	4 TRACK 4 SHUTTERS	4000	2400	30 SERIES JINDAL OR 27 SERIES GEETA	21198 (3.197 KG/M) 164.9 X 51 X 2MM THK	21204 (1.694 KG/M) 164.9 X 41 X 1.6 THK	21204 (1.694 KG/M) 164.9 X 41 X 1.6 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	CUSTOM DESIGN	CUSTOM DESIGN 210 MM X 55 MM X 2 MM THK HOLLOW SECTION SS TIP TRACKS			CUSTOM DESIGN 75 MM X 50 MM X 1.8 MM THK HOLLOW SECTION WITH STIFFNERS			SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SD3	3 TRACK 3 SHUTTERS	3000 TO 3500	2400	30 SERIES JINDAL OR 35X75 SERIES GEETA	20928 (2.032 KG/M) 124 X 51 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	CUSTOM DESIGN	CUSTOM DESIGN 170 MM X 40 MM X 2 MM THK HOLLOW SECTION SS TIP TRACKS			CUSTOM DESIGN 75 MM X 50 MM X 1.8 MM THK HOLLOW SECTION WITH STIFFNERS			SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SD4	3 TRACK 3 SHUTTERS	3000	2100	25 SERIES JINDAL OR 25 SERIES GEETA	20673 WITH LEG LIP (1.650 KG/M) 116 X 40 X 1.3 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	20842 (0.781 KG/M) 60 X 25 X 1.45 THK	21091 (0.776 KG/M) 50 X 25 X 1.48 THK	21056 (0.717 KG/M) 50 X 25 X 1.51 THK	SINGLE GLASS 6MM THK HEAT STRENGHTHENED GLASS TO DESIGN	30 SERIES JINDAL OR 35X75 SERIES GEETA	20928 (2.032 KG/M) 124 X 51 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SD5	2 TRACK 2 SHUTTERS	2000	2100	25 SERIES JINDAL OR 25 SERIES GEETA	20676 WITH LEG LIP (1.073 KG/M) 75 X 45.5 X 1.25 THK	20634 WITH LEG LIP (0.619 KG/M) 75 X 25.4 X 1.3 THK	20634 WITH LEG LIP (0.619 KG/M) 75 X 25.4 X 1.3 THK	20842 (0.781 KG/M) 60 X 25 X 1.45 THK	21091 (0.776 KG/M) 50 X 25 X 1.48 THK	21056 (0.717 KG/M) 50 X 25 X 1.51 THK	SINGLE GLASS 6MM THK HEAT STRENGHTHENED GLASS TO DESIGN	30 SERIES JINDAL OR 35X75 SERIES GEETA	21217 (1.502 KG/M) 83 X 52 X 1.5 THK	20835 (0.904 KG/M) 83 X 41 X 1.5 THK	20835 (0.904 KG/M) 83 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SD6	2 TRACK 2 SHUTTERS	2000	2400	30 SERIES JINDAL OR 35X75 SERIES GEETA	21217 (1.502 KG/M) 83 X 52 X 1.5 THK	20835 WITH LEG LIP (0.904 KG/M) 83 X 41 X 1.5 THK	20835 WITH LEG LIP (0.904 KG/M) 83 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 6MM THK HEAT STRENGHTHENED GLASS TO DESIGN	CUSTOM DESIGN	CUSTOM DESIGN 110 MM X 40 MM X 2 MM THK HOLLOW SECTION SS TIP TRACKS			CUSTOM DESIGN 75 MM X 50 MM X 1.8 MM THK HOLLOW SECTION WITH STIFFNERS			SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SD7	2 TRACK 4 SHUTTERS	4000	2100 TO 2400	30 SERIES JINDAL OR 35X75 SERIES GEETA	21217 (1.502 KG/M) 83 X 52 X 1.5 THK	20835 WITH LEG LIP (0.904 KG/M) 83 X 41 X 1.5 THK	20835 WITH LEG LIP (0.904 KG/M) 83 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 6MM THK HEAT STRENGHTHENED GLASS TO DESIGN	CUSTOM DESIGN	CUSTOM DESIGN 110 MM X 40 MM X 2 MM THK HOLLOW SECTION SS TIP TRACKS			CUSTOM DESIGN 75 MM X 50 MM X 1.8 MM THK HOLLOW SECTION WITH STIFFNERS			SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws

HEIGHT OF BUILDING 0 TO 70 M - GF TO 20 TH FLOOR - 1.5 Kpa												HEIGHT OF BUILDING 71 M TO 100 M - 21ST FLOOR TO 30TH FLOOR - 2 Kpa									
SLIDING WINDOW																					
SW1	3 TRACK 3 SHUTTERS	3000	1500	25 SERIES JINDAL OR 25 SERIES GEETA	20673 WITH LEG LIP (1.650 KG/M) 116 X 40 X 1.3 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	20842 (0.781 KG/M) 60 X 25 X 1.45 THK	21091 (0.776 KG/M) 50 X 25 X 1.48 THK	21056 (0.717 KG/M) 50 X 25 X 1.51 THK	SINGLE GLASS 6MM THK ANNEALED GLASS TO DESIGN	30 SERIES JINDAL OR 35X75 SERIES GEETA	20928 (2.032 KG/M) 124 X 51 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SW2	3 TRACK 3 SHUTTERS	2000	1500	25 SERIES JINDAL OR 25 SERIES GEETA	20673 WITH LEG LIP (1.650 KG/M) 116 X 40 X 1.3 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	20842 (0.781 KG/M) 60 X 25 X 1.45 THK	21091 (0.776 KG/M) 50 X 25 X 1.48 THK	21056 (0.717 KG/M) 50 X 25 X 1.51 THK	SINGLE GLASS 6MM THK ANNEALED GLASS TO DESIGN	30 SERIES JINDAL OR 35X75 SERIES GEETA	20928 (2.032 KG/M) 124 X 51 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SW3	2 TRACK 2 SHUTTERS	2000	1050 TO 1350	25 SERIES JINDAL OR 25 SERIES GEETA	20676 WITH LEG LIP (1.073 KG/M) 75 X 45.5 X 1.25 THK	20634 WITH LEG LIP (0.619 KG/M) 75 X 25.4 X 1.3 THK	20634 WITH LEG LIP (0.619 KG/M) 75 X 25.4 X 1.3 THK	20842 (0.781 KG/M) 60 X 25 X 1.45 THK	21091 (0.776 KG/M) 50 X 25 X 1.48 THK	21056 (0.717 KG/M) 50 X 25 X 1.51 THK	SINGLE GLASS 6MM THK ANNEALED GLASS TO DESIGN	30 SERIES JINDAL OR 35X75 SERIES GEETA	21217 (1.502 KG/M) 83 X 52 X 1.5 THK	20835 (0.904 KG/M) 83 X 41 X 1.5 THK	20835 (0.904 KG/M) 83 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SW4	2 TRACK 4 SHUTTERS	4000	1050 TO 1350	25 SERIES JINDAL OR 25 SERIES GEETA	20676 WITH LEG LIP (1.073 KG/M) 75 X 45.5 X 1.25 THK	20634 WITH LEG LIP (0.619 KG/M) 75 X 25.4 X 1.3 THK	20634 WITH LEG LIP (0.619 KG/M) 75 X 25.4 X 1.3 THK	20842 (0.781 KG/M) 60 X 25 X 1.45 THK	21091 (0.776 KG/M) 50 X 25 X 1.48 THK	21056 (0.717 KG/M) 50 X 25 X 1.51 THK	SINGLE GLASS 6MM THK ANNEALED GLASS TO DESIGN	30 SERIES JINDAL OR 35X75 SERIES GEETA	21217 (1.502 KG/M) 83 X 52 X 1.5 THK	20835 (0.904 KG/M) 83 X 41 X 1.5 THK	20835 (0.904 KG/M) 83 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SW5	3 TRACK 3 SHUTTERS	3000	1050 TO 1350	25 SERIES JINDAL OR 25 SERIES GEETA	20673 WITH LEG LIP (1.650 KG/M) 116 X 40 X 1.3 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	20842 (0.781 KG/M) 60 X 25 X 1.45 THK	21091 (0.776 KG/M) 50 X 25 X 1.48 THK	21056 (0.717 KG/M) 50 X 25 X 1.51 THK	SINGLE GLASS 6MM THK ANNEALED GLASS TO DESIGN	30 SERIES JINDAL OR 35X75 SERIES GEETA	20928 (2.032 KG/M) 124 X 51 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SW6	3 TRACK 6 SHUTTERS	6000	1050 TO 1350	25 SERIES JINDAL OR 25 SERIES GEETA	20673 WITH LEG LIP (1.650 KG/M) 116 X 40 X 1.3 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	21032 WITH LEG LIPS(1.01 KG/M) 116 X 25 X 1.35 THK	20842 (0.781 KG/M) 60 X 25 X 1.45 THK	21091 (0.776 KG/M) 50 X 25 X 1.48 THK	21056 (0.717 KG/M) 50 X 25 X 1.51 THK	SINGLE GLASS 6MM THK ANNEALED GLASS TO DESIGN	30 SERIES JINDAL OR 35X75 SERIES GEETA	20928 (2.032 KG/M) 124 X 51 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20837 (1.197 KG/M) 124 X 41 X 1.5 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
SW7	4 TRACK 4 SHUTTERS	4000	2400	30 SERIES JINDAL OR 27 SERIES GEETA	21198 (3.197 KG/M) 164.9 X 51 X 2MM THK	21204 (1.694 KG/M) 164.9 X 41 X 1.6 THK	21204 (1.694 KG/M) 164.9 X 41 X 1.6 THK	20772 (0.948 KG/M) 71 X 30 X 1.5 THK	21009 (0.964 KG/M) 65 X 30 X 1.5 THK	21008 (0.762 KG/M) 65 X 30 X 1.5 THK	SINGLE GLASS 6MM THK ANNEALED GLASS TO DESIGN	CUSTOM DESIGN	CUSTOM DESIGN 210 MM X 55 MM X 2 MM THK HOLLOW SECTION SS TIP TRACKS			CUSTOM DESIGN 75 MM X 50 MM X 1.8 MM THK HOLLOW SECTION WITH STIFFNERS			SINGLE GLASS 8MM THK HEAT STRENGHTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws

NOTE: SINGLE PANE OF ANNEALED GLASS FOR SLIDING / CASEMENT WINDOWS WITHIN FRAMES SHALL BE RESTRICTED TO NOT GREATER THAN 1.2 SQM IN AREA

ID MARK	CONFIGUARATION	SIZE		HEIGHT OF BUILDING 0 TO 70 M - GF TO 20 TH FLOOR - 1.5 Kpa						HEIGHT OF BUILDING 71 M TO 100 M - 21ST FLOOR TO 30TH FLOOR - 2 Kpa							
		WIDTH	HEIGHT	ALUMINIUM SECTION SERIES	OUTER FRAME	SHUTTER FRAME	CENTER MULLION	CLIP	GLASS	ALUMINIUM SECTION SERIES	OUTER FRAME	SHUTTER FRAME	CENTER MULLION	CLIP	GLASS	COATING	HARDWARE ETC
CASEMENT WINDOWS																	
CW1	SIDE HUNG 2 SHUTTERS MIDDLE + 1 FIXED & 3 +3 FIXED TOP & BOTTOM	3000	2400	CUSTOM DESIGN	80MM X 40 MM X 2 MM THK HOLLOW SECTION	80MM X 40 MM X 2 MM THK HOLLOW SECTION			SINGLE GLASS 6 MM THK HEAT STRENGTHENED GLASS TO DESIGN	CUSTOM DESIGN	80MM X 40 MM X 2 MM THK HOLLOW SECTION	80MM X 40 MM X 2 MM THK HOLLOW SECTION			SINGLE GLASS 6 MM THK HEAT STRENGTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported
CW2	SIDE HUNG 2 SHUTTERS MIDDLE FIXED	3000	1500	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK WITH STIFFNERS	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK WITH STIFFNERS	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm clear Annealed glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	CUSTOM DESIGN	80MM X 40 MM X 2 MM THK HOLLOW SECTION	80MM X 40 MM X 2 MM THK HOLLOW SECTION			SINGLE GLASS 6 MM THK HEAT STRENGTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
CW3	SIDE HUNG 2 SHUTTERS	1400	1350	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm clear Annealed glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm clear Heat Strengthened glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
CW2	SIDE HUNG 1 SHUTTER	600	1350	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm clear Annealed glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	CUSTOM DESIGN	80MM X 40 MM X 2 MM THK HOLLOW SECTION	80MM X 40 MM X 2 MM THK HOLLOW SECTION	80MM X 40 MM X 2 MM THK HOLLOW SECTION	80MM X 40 MM X 2 MM THK HOLLOW SECTION	SINGLE GLASS 6 MM THK HEAT STRENGTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
V1	SIDE HUNG 1 SHUTTER + 2F + EXHAUST	950	1650	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm ACID FROSTED Annealed glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	CUSTOM DESIGN	80MM X 40 MM X 2 MM THK HOLLOW SECTION	80MM X 40 MM X 2 MM THK HOLLOW SECTION			SINGLE GLASS 6 MM THK ACID FROSTED HEAT STRENGTHENED GLASS TO DESIGN	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
V2	SIDE HUNG 1 SHUTTER + 1F + EXHAUST	700	1650	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm ACID FROSTED Annealed glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm ACID FROSTED Heat Strengthened glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws
V3	SIDE HUNG 1 SHUTTER + 1F + EXHAUST	600	1350	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm ACID FROSTED Annealed glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	CASEMENT WINDOW SERIES B OF JINDAL OR 52 MM SPECIAL OPENABLE WINDOW SERIES	20558 (0.534 KG/M) 42 X 31 X 1.6 MM THK	20559 (0.724 KG/M) 42X 46.2 X 1.5 MM THK	20560 (0.764 KG/M) 42 X 46.2 X 1.6 THK	19391 (0.289 KG/M)28 X 15.3 X 1.5 MM THK	6mm ACID FROSTED Heat Strengthened glass (Saint Gobain/ Asahi/ Modi/or approved equal make)	JOTUN or AKZONBLE Brand 50 micron Colour Powder Coating as per the approved shade	Lock: Alualpha FLUSH MOUNTED TONGUE LOCK WITH SOCKET ROLLER Bearing: NSK JAPAN OF CAPACITY WT OF SHUTTER Woolpile: Imported EPDM Gaskets SS screws

NOTE: SINGLE PANE OF ANNEALED GLASS FOR SLIDING / CASEMENT WINDOWS WITHIN FRAMES SHALL BE RESTRICTED TO NOT GREATER THAN 1.2 SQM IN AREA